


Wavelength	Type	Technology	Case
Red	water clear	AlGaAs/GaAs	3 mm plastic lens

**Description**

Selective photodiode mounted in standard 3 mm package with standoff. Narrow response range (660 nm peak) by means of integrated filter

Note: Special packages without standoff available on request

Applications

Optical communications, safety equipment, automation, analytics

Miscellaneous Parameters

$T_{amb} = 25^{\circ}\text{C}$, unless otherwise specified

Parameter	Test conditions	Symbol	Value	Unit
Active area		A	0.17	mm ²
Temperature coefficient of I_D		$T_C(I_D)$	4	%/K
Operating temperature range		T_{amb}	-20 to +85	$^{\circ}\text{C}$
Storage temperature range		T_{stg}	-40 to +100	$^{\circ}\text{C}$
Soldering Temperature	$t \leq 3 \text{ s}$, 3 mm from case	T_{sld}	260	$^{\circ}\text{C}$
Acceptance angle at 50% S_{λ}		φ	60	deg.

Optical and Electrical Characteristics

$T_{amb} = 25^{\circ}\text{C}$, unless otherwise specified

Parameter	Test conditions	Symbol	Min	Typ	Max	Unit
Breakdown voltage ¹⁾	$I_R = 10 \mu\text{A}$	V_R	5			V
Dark current	$V_R = 1 \text{ V}$	I_D		40	200	pA
Peak sensitivity wavelength	$V_R = 0 \text{ V}$	λ_p		660		nm
Responsivity at λ_p	$V_R = 0 \text{ V}$	S_{λ}		0.42		A/W
Sensitivity range at 1% ¹⁾	$V_R = 0 \text{ V}$	$\lambda_{min}, \lambda_{max}$	605		705	nm
Spectral bandwidth at 50%	$V_R = 0 \text{ V}$	$\Delta\lambda_{0.5}$		80		nm
Shunt resistance	$V_R = 10 \text{ mV}$	R_{SH}	500	670		G Ω
Noise equivalent power	$\lambda = 660 \text{ nm}$	NEP		8.5×10^{-15}		W/ $\sqrt{\text{Hz}}$
Specific detectivity	$\lambda = 660 \text{ nm}$	D^*		4.8×10^{12}		$\text{cm} \cdot \sqrt{\text{Hz}} \cdot \text{W}^{-1}$
Junction capacitance	$V_R = 0 \text{ V}$	C_J		50		pF
Switching time ($R_L = 50 \Omega$)	$V_R = 1 \text{ V}$	t_r, t_f		15/30		ns
Photo-current at illuminant A ^{1,2)}	$V_R = 0 \text{ V}$ $E_v = 1000 \text{ lx}$	I_{Ph}		0.33		μA

¹⁾for information only

²⁾ Standard light source with a color temperature of 2856 K

Note: All measurements carried out with *EPIGAP* equipment

Labeling

Type	Lot N°	R_D (typ.) [G Ω]	Quantity
EPD-660-3-0.5			

