

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
WELCH ALLYN, INC. AND SHALL NOT BE REPRODUCED, OR COPIED,
OR USED AS A BASIS FOR MANUFACTURE OR SALE OF EQUIPMENT
OR DEVICES WITHOUT WRITTEN PERMISSION.

		16300234		
REV	REVISION DESCRIPTION	ECN	DATE	APPROVAL

1. LAMP TYPE

LENSED END, C-6 FILAMENT, GAS FILLED,
SUBMINIATURE TWO-PIN CONSTRUCTION

2. RATED VOLTAGE

5.0 ±.01 VOLTS D.C.

3. CURRENT

.970 ±5% AMPERES

4. COLOR TEMPERATURE

2800 °K AT FILAMENT CENTER COILS OUTER
DIAMETER USING A TELESCOPING OPTICAL
PYROMETER

5. MEAN SPHERICAL CANDLEPOWER


3.3 ±12% MSCP (WIRE TERMINAL LAMP IN A
20" INTEGRATING SPHERE)

6. DESIGN LIFE

10,000 HOURS AVERAGE

7. SPOT SIZE

.140" NOMINAL DIA. TANGENT TO THE LENS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DRAWN <i>PMB</i>	DATE <i>2/4/93</i>	WELCH ALLYN, INC. SKANEATELES FALLS, NY U.S.A.			
TOLERANCES ON:			CHECKED <i>CFC</i>	<i>2/4/93</i>				
BASIC DIMENSION	.XX	.XXX	APPROVED <i>JWH</i>	<i>2/16/93</i>	TITLE: <i>LAMP SPECIFICATIONS FOR SK-DAB-01206</i>			
UP TO 6	±.02	±.005	REL. FOR PROD. <i>DAB</i>	<i>2/16/93</i>				
ABOVE 6 TO 24	±.03	±.010	DO NOT SCALE		CODE IDENT <i>64475</i>		DRAWING NO. <i>16300234</i>	REV.
ABOVE 24	±.06	±.015			SCALE			
ANGLES ± 1/2 DEGREE							SHEET	OF